

		METRIC		U.S.	
Key Specifications	Machine weight	1200	kg		lb.
	Bucket capacity	0.02	m³	0.026	yd³
	Width of bucket	430	mm	17	in.
Engine	Make / Model	YANMAR 3TNV70			
	Number of cylinders	3		3	
	Rated power, net (SAE J1995)	10.3kW / 2200	kW/rpm	14 hp at 2200	hp/rpm
Performance parameter	Max. Gradeability	30	°	30	°
	Max. digging force of arm	6	kN	1349	lbf.
	Max. digging force of bucket	10	kN	2248	lbf.
	Traveling speed	2 / 4	km/h	1.2 / 2.5	mph
	Max. hauling force	19	kN	4271	lbf.
	Slewing speed of platform	8.5-10.5	rpm	8.5-10.5	rpm
Operating parameter	Max. digging height	3062	mm	10'0"	ft. in.
	Max. digging depth	1830	mm	6'0"	ft.in
	Max. digging radius	3493	mm	11'6"	ft.in
	Max. digging radius on ground level	3542	mm	11'7"	ft.in
	Max. dumping height	2075	mm	6'10"	ft.in
	Max. vertical digging depth	1613	mm	5'4"	ft.in
Transportation dimension	Overall length	3070	mm	10'0"	ft.in
	Overall width	50 / 1100	mm	2'9" / 3'7"	ft.in
	Overall height	2458	mm	8'0"	ft.in
Other Parameter	Length of track	1404	mm	4'7"	ft.in
	Width of track	180	mm	7.1	in
	Ground clearance	120	mm	4.7	in
	Fuel tank capacity	13	L	3.4	gal.
	Hydraulic oil tank capacity	13.5	L	3.5	gal.
	Boom Swing - Left/right	65°/55°			°
	Working Pressure	18	Mpa	2610	psi
	Dozer size (width × height)	990 x 220	mm	39 x 8.7	in.
	Flow rate	21	L/Min	5.5	gpm

Boleo® reminds users to read and understand the operator's manual before operating any euipment. Aso,make sure all safety devices and shields are in place and functioning properly.

Boleo® reserves the right to add improvements or make changes in specifications at any time without notice or obligaion.